



COMMERCIAL LVT / GLUE DOWN

TECHNICAL DATA SHEET

ITEM	EN NORMS	RESULT	ASTM NORMS	RESULT	REMARK
Size	EN 427	1227*187 mm	ASTM F536	1227*187 mm	Pass
Dimension Squareness and Straightness	EN 427	Squareness: 0.18 mm Straightness: 0.07 mm			Pass
Chemical Resistance	EN 423	Pass	ASTM F925	Pass	available upon request
Color Fastness to Artificial light	EN 20105:B02 method A	Pass, >=Grade6	ASTM F1515	Pass	available upon request
Wear Resistance	EN 660-1	Weargroup: T			available upon request
Resistant to impact			ASTM F1265	Pass	available upon request
Dimensional Stability	E434	Pass	ASTM F1700	Pass	
Residual Indentation	EN 433	Pass	ASTM F970	Pass	
Slip Resistance	EN 13893	Class DS			
Behaviour to Fire	EN 13501-1	Bf1-S1	ASTM E648-06	Pass/Class 1	
Smoke Density			ASTM E662	Pass, <=450	

2.5mm



20 Mil wear layer





COMMERCIAL LVT / GLUE DOWN

SPECIFICATIONS

Material	LVT
Length x Width (mm)	1227*187 mm
Gloss level	SP 5-7
UV matt coating	Yes, SP coating
Pieces / Carton	16
Cartons / Pallet	50
Overall thickness (mm)	2.5 mm
Virgin materials	Yes
Installation	Glue Down
Square Feet / Carton	39.52
Square Feet / Pallet	1956
Wear layer	20 Mil (0.5 mm)
Bevel edges on 4 sides	Micro Bevel
Click system	NO
Weight Pounds/ Piece	2.64
Weight Pounds/ Box	43.47



2.5mm



20 Mil
wear layer

